



STANDARD COLOR CHART

PROUDLY FINISHED WITH
SHERWIN-WILLIAMS®
Coil Coatings

WARNING: Please be aware that there will be some color variation due to digital scanning, your monitor settings, printer quality, etc. If you are trying to match an existing color, we recommend that you request a hard copy of this chart.

WeatherXL™ Siliconized-Modified Polyester (SMP)



Ash Gray
SR 0.46 SRI 52



Black
SR 0.31 SRI 31



Burnished Slate
SR 0.34 SRI 35



Charcoal Gray
SR 0.37 SRI 31



Charcoal Blue Gray
SR 0.29 SRI 29



Rustic Red
SR 0.36 SRI 38



Crimson Red
SR 0.31 SRI 31



Desert Sand
SR 0.42 SRI 47



Evergreen
SR 0.35 SRI 37



Gallery Blue
SR 0.26 SRI 24



Light Stone
SR 0.56 SRI 65




Old Town Gray
SR 0.41 SRI 45



Polar White
SR 0.64 SRI 77



Saddle Tan
SR 0.47 SRI 53



Solar White
SR 0.71 SRI 86



Galvalume
SR 0.65 SRI 60

Fluropon® 70% PVDF



Almond
SR 0.64 SRI 60



Ash Gray
SR 0.34 SRI 34



Brownstone
SR 0.40 SRI 40



Charcoal Gray
SR 0.33 SRI 33



Colonial Red
SR 0.35 SRI 29




Copper Metallic
SR 0.51 SRI 58



Dark Bronze
SR 0.24 SRI 23



Evergreen
SR 0.24 SRI 22



Matte Black
SR 0.25 SRI 25




Medium Bronze
SR 0.30 SRI 27



Regal Blue
SR 0.25 SRI 24



Regal Red
SR 0.49 SRI 48




Regal White
SR 0.85 SRI 83



Sandstone
SR 0.53 SRI 52



Slate Gray
SR 0.15 SRI 15



Snow White
SR 0.75 SRI 73

WARNING: Please be aware that there will be some color variation due to digital scanning, your monitor settings, printer quality, etc. If you are trying to match an existing color, we recommend that you request a hard copy of this chart.



STEEL BUILDINGS, INC

PO BOX 2314 • 2705 AVALON AVENUE • MUSCLE SHOALS, ALABAMA 35662 • PHONE 256-383-7322 or 800-633-3378

www.bigbee.com • sales@bigbee.com





STANDARD COLOR CHART

PROUDLY FINISHED WITH
SHERWIN-WILLIAMS
Coil Coatings

PANEL OFFERINGS

Profile	26 Gauge			24 Gauge			
	Galvalume®	WeatherXL™ (SMP)	Fluropon® (70% PVDF)	Galvalume®	WeatherXL™ (SMP)	Fluropon® (70% PVDF)	
RIB II PBR RR	●	●	N/A	●	2.	●	
LOK-324	N/A	N/A	N/A	●	1.	●	
VR-216	N/A	N/A	N/A	●	1.	●	
VR-218	N/A	N/A	N/A	●	1.	●	

1. Available in Solar White only.
2. Available in Polar White and Solar White only.

- Final color selection should be made from actual color chips.
- Additional cost will apply to all Fluropon 70% PVDF (containing Kynar 500®) coatings.
- Visit our website www.bigbee.com for the most current information.

Solar Reflectivity (SR)

Solar reflectivity or reflectance (SR) is the ability of a material to reflect solar energy from its surface back into the atmosphere. The SR value is a number from 0 (zero) to 1.0. A value of 0 indicates that the material absorbs all solar energy and a value of 1.0 indicates it is all reflected.

Solar Reflectance Index (SRI)

The Solar Reflectance Index (SRI) is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. Emissivity is a material's ability to release absorbed energy. To meet LEED requirements a roofing material must have an SRI of 29 or higher for steep slope roofing (above 2:12) and an SRI value of 78 or higher for low slope roofing (2:12 or less). For more information, please visit www.usgbc.org.

Sherwin-Williams®, Fluropon®, WeatherXL™ are trademarks of SWIMC LLC • Galvalume® is a registered trademark of BIEC International, Inc. Kynar 500® is a registered trademark of Arkema, Inc.



PO BOX 2314 • 2705 AVALON AVENUE • MUSCLE SHOALS, ALABAMA 35662 • PHONE 256-383-7322 or 800-633-3378
www.bigbee.com • sales@bigbee.com

